


PRODUCT NAME:

VELCRO SHEET

PRODUCT CODE/S:
PREPACKED 5 PER PACK 115X230: PPA020, PPA021, PPA022, PPA023,
50PER PACK 115X230 : AP180, AP181, AP182, AP183, AP184

KEY FEATURES:



- Safeline Hook and loop backing. High performance aluminium oxide grain.
 Punched sanding sheets for use on wood, metal, plaster and filler.
- Hole configuration helps remove dust as you sand.
 - Perfect for material shaping and smoothing
 - For use on wood, metal, plaster and filler.

MATERIAL:
Aluminium Oxide

This man-made material is suitable for shaping, sanding and polishing hard metal such as iron and steel, but also effective on timber. Aluminium oxide cuts much faster and lasts longer than glass or garnet.
 It is available on non-waterproof, cloth or waterproof backings.

SIZE CHART

GRIT SIZE	GRADE	CODES	SIZE	APPLICATION
40-60	COARSE	PPA022, AP180, AP181	115MM X 230	MATERIAL REMOVAL
80-100	MEDIUM	PPA021, AP182, AP194	115MM X 230	LEVELING
120-UPWARDS	FINE	PPA020, AP184	115MM X 230	FINISHING
40-60	COARSE	AP063, AP064	115MM X 280	MATERIAL REMOVAL
80-100	MEDIUM	AP065, AP066	115MM X 280	LEVELING
120-UPWARDS	FINE	AP067	115MM X 280	FINISHING


STORAGE

IT IS RECOMMENDED THAT ALL COATED ABRASIVE PRODUCTS SHOULD BE STORED AT CONSTANT LEVELS OF TEMPERATURE AND HUMIDITY WITHIN THE RANGES OF 18-22°C, 50-65% RH. THEY SHOULD BE KEPT AWAY FROM DAMP (OR COLD) WALLS, WINDOWS OR FLOORS TO AVOID POSSIBLE MOISTURE ABSORPTION. EQUALLY STORAGE ADJACENT TO HEAT SOURCES E.G. STEAM PIPES, RADIATORS, HOT AIR DUCTS, OVENS, ETC.,

