

DATA SHEETS



PRODUCT NAME:

EVERBUILD 825 SILICONE 380ML

PRODUCT CODE/S:

BROWN	
EB825ANTH	EVERBUILD 825 SILICONE ANTHRACITE 380ML
EB825BEI	EVERBUILD 825 SILICONE BEIGE 380ML
EB825BLK	EVERBUILD 825 SILICONE BLACK 380ML
EB825BRIRED	EVERBUILD 825 SILICONE BRICK RED 380ML
EB825BRW	EVERBUILD 825 SILICONE BROWN 380ML
EB825BUFF	EVERBUILD 825 SILICONE BUFF 380ML
EB825DGREY	EVERBUILD 825 SILICONE DARK GREY 380ML
EB825LWHE	EVERBUILD 825 SILICONE LIMESTONE WHITE 380L
EB825MAGN	EVERBUILD 825 SILICONE MAGNOLIA 380ML
EB825MGREY	EVERBUILD 825 SILICONE MID GREY 380ML
EB825PORT	EVERBUILD 825 SILICONE PORTLAND STONE 380ML
EB825WHE	EVERBUILD 825 SILICONE WHITE 380ML

DETAILS:

Full Description:

Everbuild 825 Silicone is a low modulus neutral cure (LMN) silicone sealant designed for use in structural
glazing, curtain walling, and perimeter joint sealing. It adheres to most common building materials without the need for primer, including glass, aluminium, PVCu, and masonry.

Its high movement capability (±25%) makes it perfect for expansion joints, while its UV and weather resistance ensures long-lasting performance in both internal and external applications. Everbuild 825 is also non-corrosive, making it suitable for use around sensitive metals and finishes.

Application Area

Sealing expansion and movement joints in construction

Perimeter sealing of window and door frames

Curtain walling and structural glazing systems

Metal cladding and panels

Masonry and concrete joints

Weatherproofing external joints and facades

Key Features:

Low modulus neutral cure (LMN) silicone
Excellent movement accommodation (up to ±25%)
Adheres to most substrates without priming
Non-corrosive – safe for use on metals
UV and weather resistant – suitable for outdoor use
Highly flexible – ideal for movement joints
Low shrinkage – long-lasting seal
Permanently elastic after curing
Available in multiple colours (white, grey, black, etc.)

STANDARDS

EN 15651-1