



PRODUCT NAME:

EVERBUILD GENERAL PURPOSE SILICONE GREY 310M

PRODUCT CODE/S:

EBGPG

KEY FEATURES:

EVERBUILD GENERAL PURPOSE SILICONE IS A MID-MODULUS ACETOXY CURE SILICONE SEALANT DESIGNED FOR A WIDE RANGE OF SEALING AND GLAZING APPLICATIONS. IT PROVIDES A PERMANENTLY FLEXIBLE, WEATHER-RESISTANT SEAL SUITABLE FOR BOTH INTERNAL AND EXTERNAL USE.

- **PERMANENTLY FLEXIBLE:** MAINTAINS ELASTICITY FOR LONG-LASTING SEALS
- WEATHER-RESISTANT:** SUITABLE FOR EXTERIOR APPLICATIONS.
- EXCELLENT ADHESION:** BONDS WELL TO GLASS, CERAMICS, ALUMINIUM, AND NON-POROUS SURFACES.
- MOULD RESISTANT:** CONTAINS A FUNGICIDE TO PREVENT MOULD GROWTH.
- QUICK CURING:** FORMS A SKIN IN APPROXIMATELY 10 MINUTES.
- COLOR:** GREY

DETAILS:

TECHNICAL SPECS:

- Curing System:** Acetoxy
- Skin Formation Time:** Approximately 10 minutes at 20°C
- Full Cure:** 1-2mm per 24 hours
- Movement Capability:** ±12.5%
- Application Temperature:** +5°C to +40°C
- Service Temperature:** -40°C to +150°C

IDEAL FOR:

- Sealing around windows and doors
- Glazing applications
- Kitchen and bathroom sealing
- General household draught-proofing
- Internal and external joints in buildings

INSTRUCTION FOR USE:

- **Surface Preparation:**
Ensure surfaces are clean, dry, and free from dust, grease, and any old sealant or debris.
- Application:**
Cut the cartridge tip and attach the nozzle.
Apply using a standard sealant gun.
Smooth the sealant within 5-10 minutes of application using a wet finger or finishing tool.
- Curing:**
Allow to cure fully – avoid water exposure until the sealant has fully set (typically 24 hours for 2 mm thickness).
- Clean-up:**
Excess uncured silicone can be cleaned using Everbuild Wonder Wipes or white spirit.

STANDARDS

EN 15651