



PRODUCT NAME:

SIKA SANITARY SEALANT WHITE 300ML

PRODUCT CODE/S:

EBSIKASANW

KEY FEATURES:

SIKA SANITARY SEALANT WHITE 300ML IS A PREMIUM-GRADE SILICONE SEALANT SPECIFICALLY FORMULATED FOR SANITARY APPLICATIONS IN AREAS EXPOSED TO MOISTURE. IDEAL FOR USE AROUND BATHTUBS, SHOWERS, SINKS, AND TOILETS, IT PROVIDES A DURABLE, WATERPROOF SEAL THAT RESISTS MILDEW, MOLD, AND BACTERIA GROWTH, ENSURING A HYGIENIC AND CLEAN ENVIRONMENT. ITS WHITE COLOR BLENDS WELL WITH CERAMIC FIXTURES AND TILES, MAKING IT A PERFECT CHOICE FOR MODERN BATHROOMS AND KITCHENS. THE SEALANT IS EASY TO APPLY, OFFERING EXCELLENT ADHESION TO TILES, GLASS, CERAMICS, AND PLASTIC. ONCE CURED, IT REMAINS FLEXIBLE AND LONG-LASTING, EFFECTIVELY PREVENTING WATER INGRESS AND POTENTIAL DAMAGE TO WALLS AND FLOORS.

- MILDEW-RESISTANT FORMULA TO PREVENT MOLD AND BACTERIA GROWTH
WATERPROOF AND WEATHERPROOF FOR USE IN WET ENVIRONMENTS
EXCELLENT ADHESION TO TILES, CERAMICS, GLASS, PLASTICS, AND MOST BUILDING MATERIALS
FLEXIBLE AND DURABLE FOR LONG-LASTING SEALS
WHITE COLOR MATCHES CERAMIC FIXTURES AND TILES
IDEAL FOR SEALING AROUND BATHTUBS, SHOWERS, SINKS, AND TOILETS
EASY TO APPLY WITH A SMOOTH FINISH
NON-TOXIC AND SAFE FOR USE IN DOMESTIC ENVIRONMENTS
NON-CORROSIVE AND SAFE FOR CONTACT WITH MOST COMMON MATERIALS

DETAILS:

TECHNICAL SPECS:

Type: Silicone-based sealant

Size: 300ml cartridge

Color: White

Skinning Time: Approximately 10-15 minutes

Curing Time: Fully cured in 24 hours (depending on environmental conditions and joint depth)

Shore A Hardness: 20-25

Elasticity: Excellent (up to 25% joint movement accommodation)

Temperature Resistance: -40°C to +120°C (continuous)

Application Temperature: +5°C to +40°C

IDEAL FOR:

- Sealing around bathtubs, showers, sinks, and toilets in wet areas
- Kitchens and bathrooms to prevent water damage and mold growth
- Sealing tiles, glass, and ceramic surfaces exposed to moisture
- Joint sealing in areas subject to frequent water exposure
- Sealing in domestic and commercial sanitary installations
- Sealing gaps and joints in plumbing and sanitary installations

INSTRUCTION FOR USE:

- Surface Preparation: Clean and dry the surfaces to remove any dust, grease, or loose debris. For best adhesion, lightly roughen non-porous surfaces such as glass or plastic.
Application: Cut the tip of the cartridge to the desired bead size and load into a caulking gun. Apply the sealant evenly into the joint or gap, ensuring full contact with both surfaces.
Tooling: Smooth the applied sealant with a dampened tool or finger to achieve a clean and uniform finish.
Curing: Allow the sealant to cure for 24 hours for full hardness. The sealant skins over in about 10-15 minutes but requires full curing time.
Clean-up: Clean any excess sealant with a damp cloth before it cures. Once cured, the sealant can only be removed mechanically.

STANDARDS

EN 15651-1