



**PRODUCT NAME:**

EVERBUILD WEATHERMATE SEALANT BLACK 300ML

**PRODUCT CODE/S:**

EBWEATHER

**KEY FEATURES:**

EVERBUILD WEATHER MATE SEALANT BLACK 300ML IS AN ADVANCED ISOCRYLIC-BASED SEALANT FORMULATED FOR ALL-WEATHER PERFORMANCE. IT CAN BE APPLIED IN WET WEATHER AND TO WET SURFACES, MAKING IT IDEAL FOR ROOFLINE APPLICATIONS, GUTTERING, AND EXTERNAL WEATHER SEALING. THIS SEALANT REMAINS PERMANENTLY FLEXIBLE, ENSURING A DURABLE AND RELIABLE SEAL OVER TIME.

- **ALL-WEATHER APPLICATION:** CAN BE APPLIED IN WET CONDITIONS AND TO WET SURFACES.
- **PERMANENTLY FLEXIBLE:** ACCOMMODATES JOINT MOVEMENT WITHOUT CRACKING.
- **WATERPROOF:** PROVIDES A DURABLE, WEATHER-RESISTANT SEAL.
- **ADHERES TO VARIOUS SURFACES:** SUITABLE FOR USE WITH BITUMEN, ASPHALT, LEAD, GALVANIZED STEEL, AND ROOFING FELTS.
- **OVERPAINTABLE:** CAN BE PAINTED OVER WITH MOST PAINTS AND WOOD STAINS WHEN CURED.
- **EXTERNAL USE ONLY:** NOT SUITABLE FOR INTERNAL APPLICATIONS.

**DETAILS:**

**TECHNICAL SPECS:**

Type: Solvent-based isocrylic sealant.

Size: 300ml (C3 cartridge).

Color: Black.

Application Temperature: +5°C to +35°C.

Curing Time: Approximately 24 hours, depending on temperature and humidity.

Shrinkage: Approximately 25%.

Service Temperature Range: -25°C to +95°C.

Shelf Life: 12 months from the date of manufacture, if stored in unopened, original packaging in a cool, dry place.

**IDEAL FOR:**

- Roofline applications: Sealing around eaves, fascias, and soffits.
- Guttering and downpipes: Sealing joints and seams.
- External weather sealing: Around windows and doors.
- Sealing between metal, composite roof, and wall panels.
- Remedial sealing over old sealants, putties, and mastics.

**INSTRUCTION FOR USE:**

- **Surface Preparation:** Ensure all surfaces are clean, dry, and free from dust, grease, and loose particles.

**Application:** Cut the nozzle to the desired bead size and apply the sealant using a caulking gun.

**Tooling:** Smooth the applied sealant with a damp tool or finger to achieve a clean finish.

**Curing:** Allow the sealant to cure for approximately 24 hours before subjecting it to stress.

**Clean-up:** Clean tools immediately after use with an appropriate solvent.

**STANDARDS**

**EN 15651-1:2012**