

## DATA SHEETS

SEALANTS SEALANTS	PRODUCT NAME:	
	EVT BPC COLOURS RAL	
	PRODUCT CODE/S:	
	CODE	NAME
	EVTRAL1021	EVT BPC PRIME 1021 RAPE YELLOW
	EVTRAL7021	EVT BPC COLOURS RAL 7021
次	EVTRAL7028	EVT BPC COLOURS RAL 7028
CS Fair	EVTRAL7043	EVT BPC COLOURS RAL 7043
	OVERVIEW THE EVT BPC SERIES IS A PROFESSIONAL-GRADE POLYURETHANE SEALANT IDEAL FOR USE IN CONCRETE JOINTS, STRUCTURAL GLAZING, FAÇADE ELEMENTS, AND METAL CONSTRUCTION. THIS SEALANT OFFERS STRONG ADHESION, HIGH ELASTICITY, AND EXCEPTIONAL MECHANICAL RESISTANCE.	
DETAILS:		

## **Key Features:**

• Single-component, moisture-curing PU formula

Excellent adhesion on concrete, metals, wood, and plastics

Durable and highly elastic

Weather-resistant and UV stable

Available in multiple RAL colours for aesthetic consistency

Ideal for dynamic joints subject to movement

**Technical Specifications:** 

Base: Polyurethane
Packaging: 310ml cartridge
 Colours Available:
 Rape Yellow (Prime 1021)
 RAL 7021 (Black Grey)
 RAL 7028 (Moss Grey)
 RAL 7043 (Traffic Grey B)
 Skin Time: ~30 minutes
 Cure Time: ~3-4 mm/24 hrs
 Shore A Hardness: ~40
 Movement Capability: ±25%
 Temperature Resistance: -40°C to +90°C
 Application Temp: +5°C to +35°C

## **DIRECTIONS FOR USE**

1. Ensure all surfaces are clean, dry, and free of oil or dust.

Apply sealant with a suitable caulking gun.

Smooth the joint before skin formation using a spatula.

Clean excess with PU cleaner or solvent before curing.

**STANDARDS** 

EN 15651-1

sales@abcabrasives.ie