



PRODUCT NAME:

TRANSFORMER

KEY FEATURES:

CODE: T300

- 3.3KVA INTERMITTENT RATING (5 MINS ON 15 MINS OFF)
- 1.8 CONTINUOUS RATING
- PROTECTION: 10 AMP THERMAL CUT OFF
- 2 X 16 AMP 110 VOLT SOCKETS IEC60309
- CASE MANUFACTURED FROM GRP AND INSULATED TO CLASS H, ROBUST ENOUGH FOR DEMANDING OUTDOOR USE
- 1.25M 1.5MM H07RN-F CABLE



CODE: T5

- 5 KVA INTERMITTENT USE
- 3.0 KVA CONTINUOUS RATING (OVER 8 HOURS)
- THERMAL CUT OUT SWITCH – 15 AMP
- OUTER CASING MADE FROM GRP (GLASS REINFORCED PLASTIC)
- 2 X 16 AMP SOCKETS & 1 X 32 AMP SOCKET (IEC 60309)



CODE: T10

- PROTECTION: INPUT 40 AMP 2 POLE TYPE "D" MCB. OUTPUT 2 X 16 AMP, 2 X 32 AMP AND 2 POLE TYPE "D" MCB'S
- INPUT: 240V
- 4 X 16A 110V SOCKETS, 2 X 32A 110V SOCKETS



CODE: T103PHASE

- PROTECTION: INPUT 16 AMP 3 POLE TYPE "D" MCB. OUTPUT 2 X 16 AMP, 2 X 32 AMP AND 2 POLE TYPE "D" MCB'S
- INPUT: 400V
- 4 X 16A 110V SOCKETS, 2 X 32A 110V SOCKETS

STANDARDS

