

## **DATA SHEETS**

	PRODUCT NAME:		
U/P 2500LB 0030	PULL TAPE		
	PRODUCT CODE/S:		
	BCPULL: 1000M BCPULL2: 1000M		
Uma U/P 2500 R MD	KEY FEATURES:		
UP 2500LB 0001	Flat, woven, polyester tape used for installing fiber optic, copper, and coaxial cables in underground conduit. Lubricated for easy pulling and reduced friction Durably printed with sequential footage or meter markings* Available in a variety of pulling strengths from 200 to 6,000 lbs. (91-2727 kg) Low elongation for enhanced worker safety Lightweight and easily blown into conduit or innerduct Available in splice-free lengths up to 100,000 ft. (30 km) for faster, easier installation Packaged on sturdy wooden or plastic reels Easily spliced using conventional methods		
USES			

Widely used in automobile harness, wrapping of wires, insulation protection. It is the main insulation material of automobile, household electrical equipment, refrigerator, electronic apparatus, etc.

## **DETAILS**:

## POLYESTER MULETAPE PRODUCT ORDERING INFORMATION

PRO DUC T	STRENG TH lbs (kg)	TYPICAL BOWLINE STRENGTH Ibs (kg)	TYPIC AL MULEKNO T STRENG TH Ibs (kg)	MINIMUM REEL LENG THS ft (km)	MAXIMUM REEL LENG THS ft (km)	A PPRO X . WID TH
WP1250P	1250 (568)	760 (345)	900 (409)	3000 (1)	70,000 (21)	1/2"
WP2500P	2500 (1136)	1300 (591)	1800 (818)	3000 (1)	25,000 (8)	3/4"

## STORAGE

STORE UNDER NORMAL CONDITIONS OF 70°F (21°C) AND 50% R.H. IN THE ORIGINAL CARTON.