


PRODUCT NAME:

SCRIM TAPE

PRODUCT CODE/S:

AT35: 50mmX90MTR
AT48: 100mm x 90MTR
AT58: 75mm x 90MTR

KEY FEATURES:

The Safeline Self Adhesive Drywall Scrim Tape is made of tear proof woven fiberglass mesh.

It is a self-adhesive plasterboard scrim tape for the professional repair of cracks, holes and for plasterboard joints. This tape is fast, easy, extremely thin and extra strong for covering cracks, drywall joints and holes. Seals instantly without pre-pasting or stapling.

USES

Excellent holding strength
 Fast, easy & extremely thin
 Self adhesive reinforcement tape
 Seals instantly

| SPECIFICATION | ITEM | GENERAL CODE |
|--|-----------------------------|----------------|
| ITEM No. SELF-ADHESIVE MESH TAPE: | | TPCNT60-8*8 |
| WEAVE: | | Leno |
| MATERIAL (Tex): | Warp: | 66 |
| | Weft: | 66 |
| DENSITY: | Warp: | 3.2 |
| | Weft: | 3.2 |
| STANDARD WIDTH (CM.): | 5 | |
| STANDARD LENGHT (M.): | 90M | |
| GREY CLOTH WEIGHT (G/M2): | 46± 5% | |
| COATING: | acrylic self-adhesive latex | |
| WEIGHT (gr./m2): | 60 ± 5% | |
| LATEX: | ≥28% | 50M, 75M, 100M |
| THICKNESS (mm) | 0.23mm | |
| TENSILE STRENGTH (N/50mm): | ≥300 | |
| ADHESIVE TIME (SECOND) | ≥800 | |
| MOISTURE CONTENT (5%) | ≥1 | |
| CONCLUSION: THE TEST METHOD IS AS PER Q/320682SB01-1999 | | |
| BOX QTY: AT35 - 36, AT48 - 12, AT58 - 36 | | |

STORAGE

STORE UNDER NORMAL CONDITIONS OF 70°F (21°C) AND 50% R.H. IN THE ORIGINAL CARTON.