

DATA SHEETS



PRODUCT NAME:

RED SAND PAPER ROLLS

PRODUCT CODE/S:

115MMX50M: AR086, AR087, AR088, AR089, AR090, AR091, AR092, AR093, AR094, AR095, AR096, AR097

KEY FEATURES:

High-value reattachable abrasive ideal for featheredging and primer sanding
• For use on wood, metal, plaster and filler.

MATERIAL:


Aluminium Oxide

This man-made material is suitable for shaping, sanding and polishing hard metal such as iron and steel, but also effective on timber. Aluminium oxide cuts much faster and lasts longer than glass or garnet.

It is available on non-waterproof, cloth or waterproof backings.

SIZE CHART

GRIT SIZE	GRADE	CODES	SIZE	APPLICATION
40-60	COARSE	AR086, AR087	115MM X 50M	MATERIAL REMOVAL
80-100	MEDIUM	AR088, AR089	115MM X 50M	LEVELING
120 - 400 GRIT	FINE	AR090, AR091, AR092, AR093, AR094, AR095, AR096, AR097	115MM X 50M	FINISHING



STORAGE

IT IS RECOMMENDED THAT ALL COATED ABRASIVE PRODUCTS SHOULD BE STORED AT CONSTANT LEVELS OF TEMPERATURE AND HUMIDITY WITHIN THE RANGES OF 18-22°C, 50-65% RH. THEY SHOULD BE KEPT AWAY FROM DAMP (OR COLD) WALLS, WINDOWS OR FLOORS TO AVOID POSSIBLE MOISTURE ABSORPTION. EQUALLY STORAGE ADJACENT TO HEAT SOURCES E.G. STEAM PIPES, RADIATORS, HOT AIR DUCTS, OVENS, ETC.,



















