

DATA SHEETS



PRODUCT NAME:

ZIRCONIA FLAP DISCS

PRODUCT CODE/S:

115X22.2: PPA092, PPA093, PPA094, PPA095, PPA096 115X22: AD306, AD308, AD307, AD309, AD310 AD306P. AD307P. AD308P 180X22: AD316, AD317, AD311, AD312, AD315

KEY FEATURES:

Designed for grinding, blending and finishing on a wide range of metal. Hard-Wearing, Long Service Life for Our Flap Discs • Suitable for Stainless Steel also Great for Mild Steel

MATERIAL:

Zirconium is made by die-casting and is generally available in the coarser grits up to 120. It is a coarse grain that has a high heat resistance and is substantially stronger than aluminum oxide. You will commonly find Zirconia abrasives in a range of colors from light blues to vibrant greens.

SIZE CHART

GRIT SIZE	GRADE	CODES	SIZE	APPLICATION
40-60	COARSE	PPA092, PPA093	115MM X 22.2MM	MATERIAL REMOVAL
80-100	MEDIUM	PPA094, PPA095	115MM X 22.2MM	LEVELING
120-UPWARDS	FINE	PPA096	115MM X 22.2MM	FINISHING

GRADE	SIZE	CODES
Z 40	115mm X 22mm	AD306
Z 80	115mm X 22mm	AD308
Z40	115mm X 22.2mm	AD307
Z 100	115mm X 22mm	AD309
Z 120	115mm X 22mm	AD310
Z 24	180mm X 22mm	AD316
Z 36	180mm X 22mm	AD317
Z40	180mm X 22mm	AD311
Z 60	180mm X 22mm	AD312
Z 120	180mm X 22mm	AD315

GRADE	SIZE	CODES
Z 40	115mm X 22mm	AD306P
Z 60	115mm X 22mm	AD307P
Z 80	115mm X 22mm	AD308P
Z 100	115mm X 22mm	AD309P
Z 120	115mm X 22mm	AD310P



STORAGE

IT IS RECOMMENDED THAT ALL COATED ABRASIVE PRODUCTS SHOULD BE STORED AT CONSTANT LEVELS OF TEMPERATURE AND HUMIDITY WITHIN THE RANGES OF 18-22°C, 50-65% RH. THEY SHOULD BE KEPT AWAY FROM DAMP (OR COLD) WALLS, WINDOWS OR FLOORS TO AVOID POSSIBLE MOISTURE ABSORPTION. EQUALLY STORAGE ADJACENT TO HEAT SOURCES E.G. STEAM PIPES, RADIATORS, HOT AIR DUCTS, OVENS, ETC.,

